

Re: RCID Planning & Engineering
Dewatering Permit for Project U Utilities

Please accept this response letter to the comments for the subject project.

Comments are listed below followed by our responses in **bold**.

1. Name of Contractor.

Response: JCB.

2. Site location plan showing task specific dewatering locations

Response: Please see attached drawing and location map.

3. Records that indicate the presence or absence of known areas of contamination within the project, and in adjacent areas that could be impacted if dewatering operations are performed. Also, if applicable, reasonable assurance that dewatering activities will not alter the contamination plumes movement or directions.

Response: There are no active cleanup sites within a half mile radius of this location. Please reference the attached Contamination Locator Map.

4. Proposed methods of construction.

Response: The project work involves dewatering in order to construct Pool, and Splash pad. Water table will be maintained up to 12' from ground elevation for all wellpoints. Keeping the water level below the proposed infrastructure will prevent the infrastructure from being buoyant and allow for safe installation. The installation of the wellpoints and risers (12' long with 3' screens) is to be accomplished by jetting a steel jet casing or jet punch to the appropriate depth around the construction area. After removal of the jetting device, the wellpoints and risers will be centrally located in the opening and a filter pack of medium-coarse sand installed around the wellpoints for the entire length of the wellpoints. The dewatering will be done in one phase. Up to 500 lf of 6" wellpoint header will be installed around the excavation and pumped with 8" wellpoint pumps at locations shown in the attached drawing. Sump pumps may be utilized to deal with surface runoff.

5. Estimated pumping rates and duration of pumping

Response: The pumping will run for the duration of the project, which is approximately 210 days per phase

Phase 1				
Pump No.	Header Length (lf)	Number of Wellpoints (ea)	Estimate Pumping Rates (gpm)	Duration of Pumping (days)
1	320	104	275	210
2	220	74	250	210
3	160	54	250	60
4	220	74	250	30
5	100	34	250	10

6. Known Volume to be discharge from vessels installed in the wet.

Response: No vessels will be installed in the wet.

7. Estimated depth of drawdown.

Response: Estimated drawdown is up to 12 ft below existing ground.

8. Anticipated cone of influence.

Response: The anticipated cone of influence is up to 340 ft from the center of each pumped system.

9. Proposed points of discharge

Response: The turbid discharge will be conveyed to a temporary holding pond until the groundwater discharge is confirmed clean. Clean discharge for All of pumps will be directed to the Seven Seas Lagoon as shown in the plans.

10. Site water routing from excavation to stormwater retention area.

Response: The turbid discharge will be conveyed to a temporary holding pond until the groundwater discharge is confirmed clean. Clean discharge for All of pumps will be directed to the Seven Seas Lagoon as shown in the plans.

11. Proposed groundwater and surface water monitoring plans and turbidity monitoring plan

Response: Flow meters shall be installed on the discharge piping and flow readings shall be read and recorded daily. Turbidity readings shall be taken twice daily, a minimum of 4 hours apart. All monitoring information will be submitted to RCID weekly on the RCID Weekly Dewatering Report. If monitoring identifies turbidity in the discharge, the dewatering system shall be shut off and RCID contacted for assistance.


12. Any other site and task specific characteristics worthy of consideration

Response: None.

13. Hydraulic information (i.e. normal pool and seasonal high water elevations) of any wetlands and surface waters within or adjacent to the proposed dewatering activities.

Response: Water level in the Seven Seas Lagoon is estimated to be at 94' elevation.

Contamination Locator Map




March 28, 2023

DEP Cleanup Sites

 PETROLEUM

1:18,056



FDEP,DWM, Esri, NASA, NGA, USGS, FEMA, Esri
Community Maps Contributors, County of Orange, FL,
FDEP, Esri, HERE, Garmin, SafeGraph,
GeoTechnologies, Inc, METI/NASA, USGS, EPA, NPS,

Dewatering Estimate Utilizing Sichardt Equation

Phase 1

Aquifer thickness:	66 feet	(a)	20.116 meters
Aquifer Kh	25 feet/day	(a)	8.819E-05 met/sec
Excavation Trench:			
Length	775 feet	(b)	236.208 meters
Width	10 feet	(b)	3.048 meters
Dewater depth	12 feet	(c)	3.657 meters

$$R_o = 3000(H-h)\text{sqrt}(K)$$

aquifer thickness H	20.116 meters
dewater thickness h	16.458 meters

R_o 103.04 meters 338.1 feet Radius of Influence

$$r_e = \text{sqrt}((L \times W)/\pi)$$

r_e 15.138 meters 49.67 feet

Dewatering Flow Rate A direct calculation of flow rate may be derived from the following equation:

$$H^2 - h^2 = \frac{n \cdot Q}{\pi \cdot k} (\ln R_o - \ln r_e)$$

Q	$n * q = p * Kh * [(H^2 - h^2) / (\ln R_o - \ln r_e)]$				
	n*Q				
	H ² - h ²	133.767	for n =	m3/sec	GPM
	ln R _o - ln r _e	1.91793	1	1.932E-02	306.299
	p * Kh	2.771E-04	256		1.20

Dewatering Estimate Utilizing Sichardt Equation

Phase 2

Aquifer thickness:	66 feet	(a)	20.116 meters
Aquifer Kh	25 feet/day	(a)	8.819E-05 met/sec
Excavation Trench:			
Length	1120 feet	(b)	341.359 meters
Width	80 feet	(b)	24.383 meters
Dewater depth	12 feet	(c)	3.657 meters

$$R_o = 3000(H-h)\sqrt{K}$$

aquifer thickness H	20.116 meters
dewater thickness h	16.458 meters

R_o 103.04 meters 338.1 feet Radius of Influence

$$r_e = \sqrt{(L \times W) / \pi}$$

r_e 51.472 meters 168.88 feet


Dewatering Flow Rate A direct calculation of flow rate may be derived from the following equation:

$$H^2 - h^2 = \frac{n \cdot Q}{\pi \cdot k} (\ln R_o - \ln r_e)$$


$$Q = \frac{n \cdot Q}{n \cdot Q} = \frac{p \cdot Kh \cdot [(H^2 - h^2) / (\ln R_o - \ln r_e)]}{n \cdot Q}$$

$H^2 - h^2$	133.767	for n =	m3/sec	GPM	MGD:
$\ln R_o - \ln r_e$	0.69410	1	5.340E-02	846.364	1.219
$p \cdot Kh$	2.771E-04	374		2.26	





Pump No.	Header Length (ft)	Number of Wellpoints (ea)	Estimate Pumping Rate (gpm)	Duration of Pumping (days)
No. 1	320	104	250	210
No. 2	220	74	250	210
No. 3	100	34	250	60
No. 4	220	74	250	30
No. 5	100	34	250	10



TEMPORARY HOLDING POND FOR TURBIDITY

FLOW METER

MAX 9' DEPTH

MAX 15 FT WELLPOINT
AND SCREEN (MAX 12' RISER; 3' SCREEN)

SUMPS (IF NEEDED)

EX. GROUND

NOTES:


- 1. 1.5" X 12' WELLPOINTS WITH 3' SCREENS (15' TOTAL).
- 2. ONE (1) 8" THOMPSON PUMP WELLPOINT PUMP UNIT OR EQUAL RECOMMENDED.
- 3. DISCHARGE SITE WATER TO TEMPORARY HOLDING POND OR BACK INTO EXCAVATION UNTIL CLEAN. CLEAN DISCHARGE WILL BE DIRECTED TO SEVEN SEAS LAGOON.

TYPICAL TRENCH EXCAVATION FOR UTILITIES

SECTION VIEW

TITLE								SCALE		DO NOT SCALE DRAWING	
DISNEY PROJECT U DEWATERING SECTIONS								N T S			
DRAWN J. SUNHACHAWI		DATE 1/30/23		TOLERANCES				SIZE		SHEET 2 OF 2	
CHECKED		DATE						DRAWING NUMBER		REV	
APPROVED		DATE		.XX = +/- .010 .XXX = +/- .005 FRACTIONS = +/- 1/32				MACH'D SURFACE			
								125 √ OA			
								ANGULAR +/- .1 CASTINGS +/- .1 WELDMENT +/- .30 MACHINED			

The Thompson Rotary Wellpoint Pump is the "original" rotary wellpoint pump trusted by contractors worldwide for more than 30 years. The state-of-the-art 8RW-DJDS-45C-MC is specifically designed and engineered for wellpoint and sock dewatering with high air handling, large water volume and high vacuum capability.




Consult factory for other versions & options including site trailers, sound attenuation, etc.

Materials	
Type	Positive displacement, low-pulsation, self-priming, rotary lobe
Rotor	Four-lobe, single piece design with carbon steel shaft and welded carbon steel fins with polyurethane coating
Rotor Housing	Rugged, heavy-duty cast aluminum
Mechanical Seal	Oil or grease lubricated with bronze rotating and steel stationary faces
Suction Tank	A36 steel with permanent solids screen, 1-1/2" drain port, adjustable vacuum breaker valve and vacuum gauge for system diagnostics
Discharge Tank	A36 steel with canvas reinforced neoprene weighted flapper style check valve; built-in reservoir with pressure relief and 1-1/2" drain port
Wear Plate	Replaceable, 304 stainless steel
Bearings	Heavy-duty, oil bath-pressure lubricated, cylindrical roller type
Canopy	Removable drop-on sound enclosure, constructed of 18 gauge solid galvaneel shell and 1.5" thick, 8lb density mineral wool, with 5 lockable doors.

TECHNICAL SPECIFICATIONS

Suction Size	8 in (20.32 cm)	Approximate Dry Weight	4,940 lbs (2240.74 kg)
Discharge Size	8 in (20.32 cm)	Fuel Tank	127 gal (480.75 L)
Maximum Flow Capacity	1750 gpm (397 m³/h)	Fuel Consumption @ 500 rpm	2.21 gph (8.37 L/h)
Maximum Head	150 ft (45.72 m)	Maximum Lift	29 inHg (736.6 mmHg)
Maximum Solids Handling	No Solids	Fuel Economy	
Maximum Operating Speed	500 rpm	0.413 lb/hp-hr @ 2,000 rpm	
Maximum Operating Temp.	200 °F (93.33 °C)	0.394 lb/hp-hr @ 1,800 rpm	
Displacement Volume ?	275 CFM (7.79 m³/h)	0.390 lb/hp-hr @ 1,600 rpm	




Engine Specification


Engine Model	John Deere 4045TFC03, 74 hp @ 2,000 rpm	Standard Equipment	Diesel oxidation catalyst, diesel particulate filter, alternator , radiator
Type	EPA Final Tier 4, In-Line, 4-Cycle, Turbocharged, high-pressure common-rail diesel	Automatic Shutdowns	Low lube oil pressure; high water temperature

Specifications and illustrations are subject to revision without notice and without incurring any obligation for previous or subsequent equipment sold. Thompson Pump (ISO 9001:2008) makes no representation regarding the completeness or accuracy of this information and is not liable for any direct or indirect damages arising from or relating to this information or its use. Capacity & Head are shown for comparative purposes. Consult Thompson factory for exact capabilities.


Wellpoint Systems and Accessories




Typical Wellpoint
Installation and Components

A


Header Pipe – Choice of standard 6" or 8" diameters. Used to direct ground water to the pump.

D

Swing Joint – Clear flexible hose that connects the riser pipe to the header valve assembly.

B


Header Coupling – Flexible rubber sleeve with stainless steel clamps to temporarily connect header pipes.

E

Valved Swing Joint – Swing joint with an integral ball valve fitted in the center.

C

Header Valve – Adjustable plastic valves which control water and air flowing into the Header Pipe from the Wellpoints.

F

Riser Pipe – Used to lengthen the wellpoint to achieve a desired depth. Riser pipes are available in PVC and galvanized steel, and are typically between 8' and 20' in length, depending on the application (shown smaller for illustrative purposes).

The Wellpoint

The screen within the wellpoint is the quintessential component of the system.

There are several different types of wellpoints, including self-jetting, stainless steel with PVC screens, and all PVC.

Premium Wellpoint Screen

The Premium Wellpoint is the top of the line in PVC wellpoint screens for construction dewatering. The main feature of the premium wellpoint is a 1" drop tube which is inserted inside the screen, and which enables the wellpoint to draw water from the bottom end of the screen, achieving the maximum draw-down in any given situation.


Economy Wellpoint Screen

The screen of the economy wellpoint maintains structural integrity while reducing dewatering costs. Designed to be installed with a stinger, the labor productivity is high.


Flexibility is the key to dewatering productivity with the economy wellpoint from Thompson Pump.

G

H




I. Header Grommet – Rubber fitting for creating a seal between the header pipe and the swing. The lack of a valve is supplemented by integral valves in the swings.



J. Riser Top – Rubber cap for the PVC riser pipe that helps create an air tight seal when



Wellpoint Puller – The wellpoint puller is fitted over the riser pipe and tightened against the pin, then lifted by the bail (either by hand or by machine depending on the depth) to pull the wellpoint from the ground.



Jetting Equipment

All wellpoint installations are conducted utilizing jetting systems, where water is forced at high pressures through long steel tubes (or self-jetting wellpoints) to cut holes into the earth for which to insert the wellpoints. The **I. Casing** is generally used for installing wellpoints in cohesive soil conditions, such as hard pan, hard clay and course rock, which allows sanding around the wellpoint to provide maximum flow to the pump. The **II. Punch** is used for installing wellpoints into soft clay and sand to allow water to drain to the level of the wellpoint from the upper layers. The **III. Stinger** is considerably smaller and lighter, and is generally used for softer sandy soil conditions. It also helps provide an economic solution, with not only a lower rental cost, but the ability to operate them by hand without the need for a backhoe. The **IV. Jet Fitting Assembly** attaches to the water source via the elbow, and then to a self-jetting wellpoint, where the water is pressurized through the tip of the wellpoint itself.

Header Support – Bracket that supports the header pipe, with a vice that tightens over the riser pipe to stabilize the installation.

